



Li 6	Diamant	Rahmenhöhe (cm)		
		50	55	60
A	Oberrohrlänge (mm)	577	592	612
B	Sitzrohrlänge (mm)	500	550	600
C	Kettenstrebenlänge (mm)	467	467	467
D	Front Center (mm)	675	691	706
E	Radstand (mm)	1133	1149	1164
F	Steuerrohrwinkel (Grad)	70°	70°	70°
G	Sitzwinkel (Grad)	74°	74°	74°
H	Reach (mm)	413	427	441
I	Stack (mm)	651	656	661
J	Tretlagerabsenkung (mm)	70	70	70
K	Tretlagerhöhe (mm)	301	301	301
	Einstiegshöhe (mm)	728	771	816

Li 6	Trapez	Rahmenhöhe (cm)	
		49	54
A	Oberrohrlänge (mm)	577	591
B	Sitzrohrlänge (mm)	490	540
C	Kettenstrebenlänge (mm)	467	467
D	Front Center (mm)	675.3	691
E	Radstand (mm)	1133	1149
F	Steuerrohrwinkel (Grad)	70°	70°
G	Sitzwinkel (Grad)	74°	74°
H	Reach (mm)	413	426
I	Stack (mm)	651	661
J	Tretlagerabsenkung (mm)	70	70
K	Tretlagerhöhe (mm)	301	301
	Einstiegshöhe (mm)	553	552

Li 6	Wave	Rahmenhöhe (cm)		
		45	50	55
A	Oberrohrlänge (mm)	580	591	606
B	Sitzrohrlänge (mm)	450	500	550
C	Kettenstrebenlänge (mm)	467	467	467
D	Front Center (mm)	675	691	707
E	Radstand (mm)	1133	1149	1165
F	Steuerrohrwinkel (Grad)	70°	70°	70°
G	Sitzwinkel (Grad)	74°	74°	74°
H	Reach (mm)	413	424	435
I	Stack (mm)	651	665	679
J	Tretlagerabsenkung (mm)	70	70	70
K	Tretlagerhöhe (mm)	301	301	301
	Einstiegshöhe (mm)	381	381	381

**CONTOURA**